CERTIFICATE OF COMPLIANCE

Certificate Number E68029

Report Reference E68029-20071023

Date 2020-December-07

Issued to: IDEC CORP

6-64 NISHIMIYAHARA 2-CHOME YODOGAWA-KUOSAKA 532-0004 JP

This is to certify that representative samples of

PROTECTORS, SUPPLEMENTARY - COMPONENT

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in

in certain constructional features or restricted in

performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 1077 Standard for Supplementary Protectors

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program



CERTIFICATE OF COMPLIANCE

Certificate Number E68029

Report Reference E68029-20071023

Date 2020-December-07

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Component - Supplementary Protectors, Overcurrent Type, Cat. No. NC1V, followed by -1, -2, or -3, followed by 1, followed by 00, 11 or, 21, may be followed by F, may be followed by -0.1A to -30A, may be followed by S, A or M.

Component - Supplementary Protectors, Shunt Protector, Voltage Type, Cat. No. NC1V, followed by -1, -2, or -3 followed by 5, followed by 00, followed by -DC24V.

Cat. No. NC1V, followed by -2 or -3, followed by 1, followed by 00, 11, or 21, may be followed by F, may be followed by -0.1A, may by followed by S, A, or M. Contact rating: 0.1 A, 250 V ac, 50/60 Hz; Short circuit rating: 250 V ac, 2500 A.



(U_L)